



3-Way ball valve

THREADED FEMALE OUTLET - SINGLE ACTING PNEUMATIC ACTUATOR - FPM ITEM 870



| REFERENCE | DESCRIPTION | Net weight | Volumen (m ³) | Gross weight | Unidades lote |
|-----------|-------------------------------------|------------|---------------------------|--------------|---------------|
| 111V593 | V.E.3V L R/H 1" ACT.NEUM SE FPM | 0 | 0,00891 | 0 | 1 |
| 111V595 | V.E.3V L R/H 1 1/2" ACT.NEUM SE FPM | 3,4964 | 0,04460 | 4,1622 | 1 |
| 111V596 | V.E.3V L R/H 2" ACT.NEUM SE FPM | 5,439 | 0,04460 | 6,1048 | 1 |
| 111V597 | V.E.3V L R/H 2 1/2" ACT.NEUM SE FPM | 10,7559 | 0,04836 | 11,5994 | 1 |
| 111V633 | V.E.3V T R/H 1" ACT.NEUM SE FPM | 0 | 0,00891 | 0 | 1 |
| 111V635 | V.E.3V T R/H 1 1/2" ACT.NEUM SE FPM | 3,4964 | 0,04460 | 4,1622 | 1 |
| 111V636 | V.E.3V T R/H 2" ACT.NEUM SE FPM | 5,439 | 0,04460 | 6,1048 | 1 |
| 111V637 | V.E.3V T R/H 2 1/2" ACT.NEUM SE FPM | 10,7559 | 0,04836 | 11,5994 | 1 |





ITEM 870 | THREADED FEMALE OUTLET - SINGLE ACTING PNEUMATIC ACTUATOR - FPM

| VITON | r | Actuador | PESO (g) | DN | Modelo | A | B | C | D | E | PN | TIPO ROSCA |
|--------|--------|----------|----------|----|--------|-----|-----|----|-----|-----|------|------------|
| 11V593 | 1" | H050 SE | 1936 | 25 | L | 162 | 72 | 23 | 183 | 138 | PN16 | BSP |
| 11V595 | 1 1/2" | H063 SE | 3631 | 40 | L | 210 | 103 | 33 | 233 | 156 | PN16 | BSP |
| 11V596 | 2" | H075 SE | 5988 | 50 | L | 261 | 120 | 29 | 267 | 210 | PN16 | BSP |
| 11V597 | 2 1/2" | H100 SE | 11933 | 65 | L | 322 | 150 | 33 | 333 | 280 | PN10 | BSP |
| 11V633 | 1" | H050 SE | 1932 | 25 | T | 162 | 72 | 23 | 183 | 138 | PN16 | BSP |
| 11V635 | 1 1/2" | H063 SE | 3621 | 40 | T | 210 | 103 | 33 | 233 | 156 | PN16 | BSP |
| 11V636 | 2" | H075 SE | 5970 | 50 | T | 261 | 120 | 29 | 267 | 210 | PN16 | BSP |
| 11V637 | 2 1/2" | H100 SE | 11893 | 65 | T | 322 | 150 | 33 | 333 | 280 | PN10 | BSP |



Product Documents



Product Certificates

Company Certificates

