



Válvulas de bola 'Basic' bidireccional

Salida R/Hembra actuador neumático simple efecto - FPM

ITEM 676



| REFERENCIA | DESCRIPCIÓN | Peso neto | Volumen (m ³) | Peso bruto | Unidades lote |
|------------|------------------------------------|-----------|---------------------------|------------|---------------|
| 111D560 | V.B.BID.ACT.NEU S/E R/H 1/2" FPM | 1,616 | 0,01553 | 1,9427 | 1 |
| 111D561 | V.B.BID.ACT.NEU S/E R/H 3/4" FPM | 1,6755 | 0,02243 | 2,1632 | 1 |
| 111D562 | V.B.BID.ACT.NEU S/E R/H 1" FPM | 1,061 | 0,03129 | 1,634 | 1 |
| 111D563 | V.B.BID.ACT.NEU S/E R/H 1 1/4" FPM | 2,7096 | 0,03129 | 3,2826 | 1 |
| 111D564 | V.B.BID.ACT.NEU S/E R/H 1 1/2" FPM | 3,0855 | 0,03129 | 3,6585 | 1 |
| 111D565 | V.B.BID.ACT.NEU S/E R/H 2" FPM | 3,672 | 0,03648 | 4,266 | 1 |
| 111D566 | V.B.BID.ACT.NEU S/E R/H 2 1/2" FPM | 5,711 | 0,04460 | 6,405 | 1 |
| 111D567 | V.B.BID.ACT.NEU S/E R/H 3" VIT | 11,61 | 0,04460 | 0 | 1 |



ITEM 676 | Salida R/Hembra actuador neumático simple efecto - FPM

| CÓDIGO | r | Actuador | PESO (g) | DN | A | B | C | D | E | F | PN | TIPO ROSCA |
|--------|--------|----------|----------|----|-----|-----|----|-----|-----|-----|------|------------|
| 11D560 | 1/2" | H050SE | 1380 | 15 | 86 | 55 | 17 | 192 | 138 | 44 | PN16 | BSP |
| 11D561 | 3/4" | H050SE | 1424.2 | 20 | 99 | 62 | 20 | 197 | 138 | 49 | PN16 | BSP |
| 11D562 | 1" | H050SE | 1561.1 | 25 | 122 | 72 | 23 | 208 | 138 | 66 | PN16 | BSP |
| 11D563 | 1 1/4" | H063SE | 2419.85 | 32 | 131 | 88 | 26 | 248 | 155 | 71 | PN16 | BSP |
| 11D564 | 1 1/2" | H063SE | 2698.24 | 40 | 155 | 103 | 33 | 265 | 155 | 75 | PN16 | BSP |
| 11D565 | 2" | H063SE | 3252 | 50 | 180 | 120 | 29 | 307 | 155 | 89 | PN16 | BSP |
| 11D566 | 2 1/2" | H075SE | 6080 | 65 | 202 | 150 | 33 | 376 | 210 | 119 | PN10 | BSP |
| 11D567 | 3" | H100SE | 11180 | 80 | 232 | 181 | 36 | 426 | 280 | 140 | PN10 | BSP |



Documentación de Producto



Certificados de Producto

Certificados de Empresa

