



Vannes à boisseau 'Basic'

Sortie fitting-tarudée - PE - Système Basic ITEM 215



RÉFÉRENCE	DESCRIPTION	Poids net	Volume (m ³)	Poids brut	Unités par lot
1011119	VALVULA ENLACE R/FIT. 20-1/2"	0,195058	0,02244	8,29	40
1011120	VALVULA ENLACE R/FIT. 25-3/4"	0,265	0,03129	11,17	40
1011121	VALVULA ENLACE R/FIT. 32-1"	0,438567	0,04717	13,7988	30
1011122	VALVULA ENLACE R/FIT. 40-1 1/4"	0,793	0,04836	16,43	20
1011123	VALVULA ENLACE R/FIT. 50-1 1/2"	1,086387	0,04460	16,845	15
1011124	VALVULA ENLACE R/FIT. 63-2"	1,57882	0,04717	16,43	10
1011125	VALVULA ENLACE R/FIT. 75-2 1/2"	1,96	0,04717	8,6	4
1011126	VALVULA ENLACE R/FIT. 90-3"	5,658	0,03648	11,91	2
1011127	VALVULA ENLACE R/FIT. 110-4"	6,672	0,03648	7,472	1





ITEM 215 | Sortie fitting-tarudée - PE - Système Basic

CÓDIGO	f -r	PESO (g)	DN	A	B	C	D	E	PN	TIPO ROSCA
11119	20-1/2"	195	15	147	52	47	78	17	PN16	BSP
11120	25-3/4"	265	20	154	59	51	84	20	PN16	BSP
11121	32-1"	438	25	183	70	66	97	23	PN16	BSP
11122	40-1 1/4"	793	32	203	84	72	128	26	PN16	BSP
11123	50-1 1/2"	1086	40	230	99	77	142	33	PN16	BSP
11124	63-2"	1578	50	270	121	90	165	29	PN16	BSP
11125	75-2 1/2"	1960	65	323	151	121	222	33	PN10	BSP
11126	90-3"	5193	80	378	175	141	244	36	PN10	BSP
11127	110-4"	6672	100	446	210	155	307	42	PN10	BSP





Documentation Produit



Certifications de produits

Certificats d'entreprise

